

Three-wire installation terminals DLIS



Screw connection system



- Foot can be snapped on TS 35 DIN rail
- Housing made from polyamide 6.6 UL 94-V2



Connection diagram

DLIS 2.5 PE/L/NT





Three-wire installation terminal, 4 connections

DLIS 2.5 PE/L/N



Three-wire installation terminal, 5 connections

DLIS 2.5 PE/L/L



Three-wire installation terminal, 5 connections

Connection type

Size (L x W x H) with TS 35 x 7.5 mm

Screw connection

90.5 x 6 x 53

Screw connection

90.5 x 6 x 53

Screw connection

90.5 x 6 x 53

Type

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Type colour

Cat. no.

Colours available

Rated specifications acc. to

Rated voltage, V

Rated current, A

Rated wire cross-section, mm² | AWG

Rated impulse voltage, kV | Contamination degree

Plug gauge acc. to EN 60 947-1 | Flamm. class acc. to UL 94

Connection data

Single wire (solid) / Stranded mm²

Stranded/stranded (w/ferrules acc. to DIN 46 228/1) mm²

Contact wire range, mm²

Stripping length, mm

Torque, Nm | Screw

Special connection, mm

Features

Material of insulated housing | Temperature range

Number of cross-connection channels | Test pick-off

Accessories

End plate AP

Cat. no.

Fixing plate HP

Cat. no.

Insulation plate TRS

Cat. no.

Busbar Ssch

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

Cross-connector Q

Cat. no.

End stop ES

Cat. no.

Screwdriver SDB

Cat. no.

Quick marking PMC SB

Cat. no.

DLIS 2.5 PE/L/NT

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/NT BG

1410.2

Qty. 50

DLIS 2.5 PE/L/N

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/N BG

1411.2

Qty. 50

DLIS 2.5 PE/L/L

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50

DLIS 2.5 PE/L/L BG

1412.2

Qty. 50